

VAPOUR



Clear Frame With SBR Foam /
Single Clear Lens / Indirect Lower
Vents • 1650401



Clear Frame With SBR Foam / Dual
Clear Lens / Indirect Lower Vents •
1650410



Smoke Frame With SBR Foam /
Single Smoke Lens / Indirect Lower
Vents • 1650402



Smoke Frame With SBR Foam /
Dual Smoke Lens / Indirect Lower
Vents • 1650408



Accessories

- 1650016 • RX Adaptor
- 1650413 • Clear Single Lens Only
- 1650414 • Smoke Single Lens Only
- 1650411 • Clear Duo Lens Only With Equalisers
- 1650412 • Smoke Duo Lens Only With Equalisers







91 Grams - Single
96 Grams - Duo

- + LOW PROFILE AND LIGHTWEIGHT DESIGN**
- + DUO LENS: AF/AS LENS, 3.0MM POLYCARBONATE
OUTER LENS, ANTI FOG INNER LENS
AND TWIN EQUALISERS**
- + TWIN EQUALISERS REMOVE MOISTURE**

bolle
SAFETY

VAPOUR

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
VAPOUR	 Clear Frame With SBR Foam / Single Clear Lens / Indirect Lower Vents	1650401	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Clear Frame With SBR Foam / Dual Clear Lens / Indirect Lower Vents	1650410	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke Frame With SBR Foam / Single Smoke Lens / Indirect Lower	1650402	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke Frame With SBR Foam / Dual Smoke Lens / Indirect Lower Vents	1650408	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 3. Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Chemical splash protection
- Dust protection
- Spraying
- Acid and alkaline handling
- Engineering
- Milling
- Process work

MAIN MARKETS

- Petrochemical industry
- Mining
- Construction
- Paint
- Manufacturing

LENSES

- Single Lens Version: 'ALS' anti-fog/anti-scratch coating on both sides of clear lens
- Duo Lens Version: 'ALS' anti-fog/anti-scratch outer lens, anti-fog inner lens
- 100% UV 385 - Clear
- 100% UV 400 - Smoke

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **BOLLE CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Yes
FOAM	Yes
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz