

# BLADE

LIGHTWEIGHT ALL POLYCARBONATE



1668201 • Clear Lens



1668202 • Smoke Lens



1668203 • Light Smoke / Silver Flash



1668205 • Ultra Light Smoke / Silver Flash







26 g

- + LIGHT WEIGHT**
- + 10 BASE CURVE**
- + HARD COATING ON ALL FLASH LENSES FOR  
ADDED STRENGTH AND PROTECTION**
- + CRYSTAL CLEAR OPTICS IN CLEAR LENS**

**bolle**  
SAFETY

# BLADE

## LIGHTWEIGHT ALL POLYCARBONATE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
BLADE	 Clear	1668201	I0	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1668202	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Light Smoke/ Silver Flash	1668203	I2	AS/NZS 1337.1.2010	Hard Coat
	 Ultra Light Smoke / Silver Flash	1668205	I2	AS/NZS 1337.1.2010	Hard Coat

### LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

### OCULAR LENS CATEGORY:

- 0. Range of luminous transmittance 80-100% (clear).
- 2. Range of luminous transmittance 18-43% (flash).
- 3. Range of luminous transmittance 8 -18% (smoke).

### APPLICATIONS

- Assembly and production work
- Emergency response
- Drilling
- Rigging
- Driving
- Solar UV exposure

### MAIN MARKETS

- Assembly and production work
- Emergency response
- Drilling
- Rigging
- Driving
- Solar UV exposure

### LENSES

- 2mm polycarbonate
- 10 base curve
- 'ALS' Anti-fog/anti-scratch coating on both sides of lenses: Clear and Smoke
- Hard coating on all Flash lenses
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke and Flash

### CLEANING AND STORAGE

**CLEANING :** Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 10
FRAME	PC
STRAP	Non Applicable
FOAM	Non Applicable
SPARE LENSES	No

### FRAME MARKING

**AS/NZS 1337.1.2010 :** Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

14/12/2018

### ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: safety@bolle.com.au

[bollesafety.com.au](http://bollesafety.com.au)

### NEW ZEALAND:

T.: 0800 2655 369  
E: bolle@bolle.co.nz

**bolle**  
SAFETY