# COVERALL CLEAN & AUTOCLAVE

FOR «CLEAN ROOMS»

The COVERALL CLEAN & AUTOCLAVE goggles have been especially developed to guarantee high protection & comfort in risky environments, like pharmaceutics, micro-electronics or even surgery departments.





COVACLAVE



78 g



COVACLEAN



96 g

# // COVACLAVE

- CLEAN ISOPRENE STRAP
- OVERFLOW CHUTE FOR LIQUIDS
- FITS OVER PRESCRIPTION GLASSES
- + TPR FRAME / UPPER INDIRECT VENTILATION / SEALED IN THE LOWER PART
- HIGH-COMFORT AUTOCLAVABLE GOGGLE
- + ♦PLATINUM COATING (+P)

# // COVACLEAN

- CLEAN ISOPRENE STRAP
- OVERFLOW CHUTE FOR LIQUIDS
- **+** FITS OVER PRESCRIPTION GLASSES
- + PVC FRAME / UPPER & LOWER INDIRECT VENTILATION
- STERILISABLE BY GAMMA & BETA RADIATION



# COVERALL CLEAN & AUTOCLAVE

MODEL **VERSIONS** REFERENCES I FNS MARKING FRAME MARKING COATINGS Ventilated COVACLEAN 2C-1,2 😭 1 BT C€ **ASAF COVERALL** Semi-ventilated COVACLAVE Anti-scratch/Anti-fog (⁺¬) 2C-1,2 1 FT KN C€

### LENS MARKING

### Optical class symbols:

1. Continuous work

### Mechanical strength symbols:

**B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

FOR «CLEAN ROOMS»

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

### Others symbols:

- K. Resistance to surface damage by fine particles
- N. Resistance to fogging

# TECHNOLOGY



The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

aç	jе	in	g I	ЭУ	lig	ht	expo	SL

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ure, exposure to heat or corrosion etc.

- 3. Liquid droplets or splashes.
- 4. Large dust particles > 5 microns.
- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s.
- B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

# CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN 13 CODE							
	COVACLEAN	COVACLAVE					
Individual plastic bag	3660740007850	3660740000646					
5 safety goggles per box	3660740107857	3660740100643					
105 safety goggles per outer pack	3660740207854	3660740200640					

CHARACTERISTICS					
LENSES	PC - 2,2 mm - Curve 4				
FRAME	PVC (CLEAN) / TPR (CLAVE)				
TEMPLES	Non applicable				
STRAP	Adjustable/ Neoprene				
FOAM	No				
MAINTENANCE AND CLEANING	Soapy water				
STERILIZATION COVACLAVE	121° / 20 mn / 15 Cycles				

Non-contractual pictures

01/06/2020











Bollé Safety AU Pty Limited 32-40 Fairchild Street Heatherton VIC 3202 T: 1300 138 098 E: sales@bollesafety.com.au

Hong Kong Bollé Safety 818, 8/F, Ocean Centre, Harbour City, 5 Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong T.: +852 2732 5038

