

HS 66-496

300MM PULL ON STRUCTURAL FIREFIGHTERS BOOT



STYLE SPECIFICATIONS

DESCRIPTION:

Premium black leather waterproof structural firefighter's pull on boot

Colour: Black

Sizes: 3 - 15, 3½ - 14½

Standards:

AS/NZS 4821:2014

EN 15090:2012 Type 2 Structural Firefighting Footwear

Application: Firefighting

FEATURES:

- Water resistant and flame retardant leather upper.
- TECTuff® toe bumper to protect against scuffing.
- Lightweight, hi impact, non-metallic, wide profile Type 1 toe cap with a padded latex cushion liner to ensure toes not in contact with cap.
- Fully lined with SYMPATEX® water proof liner & membrane.
- Heavy duty red Nomex™ stitching.
- COMFORTcushion® Impact Absorption System with PORON™ protects the heel and ball of the foot.
- NATUREform® steel toe cap with a wide profile for greater comfort. Hi-Vis reflective safety trim.
- PORON® XRD™ flexible metatarsal protection.
- Q-Flex® non metallic penetration protection insole.
- Excellent slip resistant sole; SRC slip resistant classification.
- Electrical Hazard (EH) Protection.
- Heavy Duty Nitrile Rubber dual density sole, with an in-fill comfort layer of urethane cushioning, coupled with a high density hard-wearing nitrile rubber outsole.
- Outer-sole heat resistant to 300° Celsius surface contact.
- Sole resistant to mineral & organic oils & acids. Cut, split and crack resistant.

COMFORT TECHNOLOGY



COMFORTcushion
Impact
Absorption



NATUREform
wide profile Type
1 safety toe cap



Non-Metallic
Composite
Toecap



Water Resistant
leather



Toe Bumper



Metatarsal
protection



Midsole
penetration
protection



Waterproof
footwear

SOLING TECHNOLOGY



300°C
Heat Resistant
sole (572° F)



Abrasion
Resistant sole



Cut Resistant
sole



Slip Resistant
sole



Sole resistant to
mineral oils
and acids



Sole resistant to
organic oils
and fats



Electrical Hazard
Resistant

OLIVER FOOTWEAR



Facebook.com/oliversafetyfootwear



@oliverfootwear

Honeywell