

LADDERLINK

Fixed Ladder Bracket | Product Code: LADFX001-30



SCAN ME

Terms and Conditions



SCAN ME

Catalogue



SCAN ME

Installation Handbook



SCAN ME

Installation Video
Metal Roof



SCAN ME

Installation Video
Tiled Roof

DATA SHEET



FS 70792



- Permanent ladder bracket to suit roof pitch 20 to 30 degrees.
- Quick and easy installation.
- Essential entry point system to stabilise your ladder.
- LadderLinks have a protective membrane in the form of a powdercoat finish, this ensures your LadderLink is ready for use and ready for any additional colour matching you apply.
- LadderLinks are rated to 150kg and must only be installed to structures and fixings capable of supporting 150kg.

WHAT AM I USED FOR?

Essential entry point system to any height safety system. Made from marine grade aluminium the LadderLink is designed to support a ladder, stopping sideways movement and therefore holding the ladder in place safely.

COMPLETE UNIT - PRODUCT CODE: LADFX001-30

| Product Parts | Description | Qty | Weight (kg) |
|---------------|--|-----|-------------|
| LADFX001-30 | Ladderink: Bent for 20 to 30 degree pitch roof | 1 | 2.203 |

- ⚠ Adjusting the pitch of the LadderLink is to be done by a sheet metal fabricators' bending machine. LadderLink is made from high tensile aluminium therefore ensure the bender is set on a high radius to prevent cracking.
- ⚠ Protective coating must not be removed.

© 2018, SafetyLink Pty Ltd, Australia.

Patents: SafetyLink Pty Ltd has a multitude of patents, patents pending, design applications, trademarks and copyrighted documents both lodged and issued. Should you wish to know the progress of our intellectual property on a specific product please email us on ip@safetylink.com and quote the product code.

Doc ID: MKT-543 Version: 6.0

Asia-Pacific/The Americas
+61 249641068
info@safetylink.com

Europe/Africa/Middle East
+33 619493867
europa.sales@safetylink.com

Northern Europe
+44 7599508290
uk.sales@safetylink.com